



Product Specification

Model Name	LM035TV07HS
Description	Standard LCD Module 3.5" VGA 480x(RGB)x640 Dots
Date	2018/09/02
Version	1.0

- Preliminary Specification
- Final Product Specification

Prepared by	Checked by	Approved by
SXY 2018/09/02	SXY 2018/09/02	LX 2018/09/02

For Customer Approval

Approved By	Comment



深圳市美显实业有限公司 LCD Mall Limited

Table of Contents

1. Record of Revision	3
2. General Specifications	4
3. Input/OutputTerminals.....	5
4. Absolute Maximum Rating	6
5. Electrical Characteristics	6
6. Interface Timing	8
7. Optical Characteristics	10
8. Environmental / Reliability Tests.....	13
9. Mechanical Drawing	14
10. Packing.....	15
11. TFT-LCD Module Inspection Criteria	16
12. Precautions for Use of LCD modules.....	21



深圳市美显实业有限公司
LCD Mall Limited

1. Record of Revision

Rev	Issued Date	Description	Editor
1.0	2018/09/02	First Release.	SXY



2. General Specifications

	Feature	Spec
Characteristics	Size	3.5 inch
	Resolution	480(horizontal)*640(Vertical)
	Interface	SPI+18-BIT RGB
	Pixel pitch (mm)	0.111*0.111
	Pixel Configuration	R.G.B.-Stripe
	Display Colors	262K
	LCD Driver IC	HX8363A
	CTP Driver IC	TBD
	Viewing Direction	9 O'clock
Mechanical	LCM (W x H x D) (mm)	64.0*85.0*3.0
	Active Area(mm)	53.28*71.04
	With /Without TSP	Without TSP
	Weight (g)	TBD
	LED Numbers	6 LEDs

Note 1: Requirements on Environmental Protection: RoHs

Note 2: LCM weight tolerance: +/- 5%



3. Input/Output Terminals

LCD PIN-MAP

No.	Symbol	Description
1	GND	Power ground.
2	YU	Anode of LED backlight.
3	XR	Anode of LED backlight
4	YD	Cathode of LED backlight.
5	XL	Cathode of LED backlight.
6	GND	Power ground
7	NC	No connect
8	NC	No connect
9	GND	Power ground
10~14	NC	No connect
15	GND	Power ground.
16	NC	No connect
17	RESET	RESET PIN
18~19	NC	No connect
20	VCI	Power supply for logic
21	GND	No connect
22~27	B00~B05	Blue Data bus.
28	GND	Power ground
29~34	G00~G05	Green data bus
35	GND	Power ground
36~41	R00~R05	Red data bus
42	GND	Power ground
43	VDD	Power supply for analog
44	NC	No connect
45	GND	Power ground
46	DCLK	Pixel clock signal
47	GND	Power ground
48	ENABLE	Power ground
49	GND	Power ground
50	CS	Chip select
51	SDA	Serial data signal input/out
52	NC	No connect
53	SCL	Serial clock signal
54	VSYNC	Vertical signal YNC
55	HSYNC	Horizon signal YNC



56~57	NC	No connect
58	LED-	Cathode of backlight
59	LED+	Anode of backlight
60	GND	Power ground

4. Absolute Maximum Rating

Item	Symbol	MIN	MAX	Unit
Supply voltage for analog	Vcc	-0.3	4.6	V
Supply voltage for logic	IOVCC	-0.3	4.6	V
Supply current (One LED)	I _{LED}		30	mA
Operating temperature	T _{OP}	-20	+70	°C
Storage temperature	T _{ST}	-30	+80	°C

Note: The absolute maximum rating values of this product are not allowed to be exceeded at any times. Should a module be used with any of the absolute maximum ratings exceeded, the characteristics of the module may not be recovered, or in an extreme case, the module may be permanently destroyed

5. Electrical Characteristics

5.1 Input Power


Item	Symbol	Min	Typ	Max	Unit	Applicable terminal
Supply Voltage for Analog	VCC	2.5	2.8	3.3	V	
Supply Voltage for Logic	VCI	1.65	1.8/2.8	3.3	V	
Input Voltage	V _{IL}	GND	-	0.3VCI	V	
	V _{IH}	0.8VCI	-	VCI		
Input leakage Current	I _{LKG}	-1		1	uA	

5.2 Backlight Driving Conditions

Item	Symbol	Value			Unit	Remark
		Min	Typ	Max		
Voltage for LED Backlight	V _F	18.0	19.2	20.4	V	I _L =120mA
Current for LED Backlight	I _L		20	30	mA	
Power Consumption	P		0.384		W	
LED Life Time		30000	-		Hr	Note

Note: Brightness to be decreased to 50% of the initial value at ambient temperature TA=25°C

5.3 Block Diagram



6. Interface Timing

6.1 SPI interface characteristics




Figure 8.2: DBI Type C interface characteristics

(V_{SA}=0V, VDD1=1.8V, VDD2=2.8V, VDD3=2.8V, T_A = 25°C)

Signal	Symbol	Parameter	Min.	Max.	Unit	Description
NCS	t_{css}	Chip select setup time (Write)	15	-	ns	
	t_{csH}	Chip select setup time (Read)	15	-	ns	
DNC_SCL (Write)	t_{wc}	Write cycle	80	-	ns	
	t_{wrh}	Control pulse "H" duration	30	-	ns	
	t_{wrl}	Control pulse "L" duration	30	-	ns	
DNC_SCL (Read)	t_{rc}	Read cycle	150	-	ns	
	t_{rdH}	Control pulse "H" duration	60	-	ns	
	t_{rdL}	Control pulse "L" duration	60	-	ns	
SDI (Input)	t_{ds}	Data setup time	10	-	ns	For maximum C _i =30pF For minimum C _i =8pF
	t_{dc}	Data hold time	10	-	ns	
SDO (Output)	t_{racc}	Read access time	10	60	ns	
	t_{od}	Output disable time	15	100	ns	

Note: The input signal rise time and fall time (tr, tf) is specified at 10 ns or less.

Logic high and low levels are specified as 30% and 70% of VDD1 for input signals.

Table 8.1: DBI-Type C interface characteristics

6.2 RGB interface characteristics




Figure 8.3: DPI interface characteristics

Resolution=480x854 (VSSA=0V, VDD1=1.8V, VDD2=2.8V, VDD3=2.8V, T_A=25°C)

Item	Symbol	Condition	Min.	Typ.	Max.	Unit
Vertical sync. Setup time	VSST	-	10	-	-	ns
Vertical sync. Hold time	VSHT	-	10	-	-	ns
Horizontal sync. Setup time	HSST	-	10	-	-	ns
Horizontal sync. Hold time	HSHT	-	10	-	-	ns
Pixel clock cycle When RGB I/F is running	DCKCYC	VRR ⁽⁵⁾ = Min. 50 Hz Max. 70 Hz	29.1 (Note 3)	-	46.2 (Note 4)	ns
Pixel clock low time	DCKLTL	-	10	-	-	ns
Pixel clock high time	DCKHHT	-	10	-	-	ns
Data setup time DB[23:0]	DST	-	10	-	-	ns
Data Hold time DB[23:0]	DHT	-	10	-	-	ns

Note: (1) Signal rise and fall times are equal to or less than 20 ns.

(2) Input signals are measured by 0.30 x VDD1 for low state and 0.70 x VDD1 for high state.

(3) 34.3 MHz

(4) 21.0 MHz

(5) VRR : Vertical Refresh Rate, equal to VSYNC frequency.



7. Optical Characteristics

ITEM	SYMBOL	CONDITIONS	SPECIFICATIONS			UNIT	NOTE	
			MIN	TYP	MAX			
Luminance	L	IL=20mA	460	570	680	Cd/m ²		
Contrast Ratio	CR	$\theta=0^\circ$	40	500				
Response Time	T _{ON}	25°C		25	35	ms		
	T _{OFF}							
CIE Color Coordinate	Red	X _R						
		Y _R						
	Green	X _G						
		Y _G						
	Blue	X _B						
		Y _B						
White	X _W		0.293	0.313	0.333			
	Y _W		0.337	0.357	0.377			
Viewing Angle	Hor	θ_{x+}		70		Degree	Gray Scale inversion	
		θ_{x-}		60				
	Ver	θ_{y+}	CR ≥ 10		70			
		θ_{y-}			70			
Uniformity	Un			80		%		

Note1. Definition of contrast ratio

Contrast ratio(Cr) is defined mathematically by the following formula. For more information see FIG.2.

$$\text{Contrast ratio} = \frac{\text{Luminance measured when LCD on the "White" state}}{\text{Luminance measured when LCD on the "Black" state}}$$

For contrast ratio, Surface Luminance, Luminance uniformity and CIE,the testing data is base on TOPCON's BM-5 or BM-7 photo detector or compatible.

Note2. Definition of surface luminance.

Surface luminance is the luminance with all pixels displaying white. For more information see FIG.2.

$$L_v = \text{Average Surface Luminance with all white pixels}(P_1, P_2, P_3, \dots, P_n)$$

Note3. Definition of luminance uniformity

The luminance uniformity in surface luminance is determined by measuring luminance at each test position 1 through n, and then dividing the maximum luminance of n points luminance by minimum luminance of n points luminance.For more information see FIG.2.

$$YU = \frac{\text{Minimum surface luminance with all white pixels } (P_1, P_2, P_3, \dots, P_n)}{\text{Maximum surface luminance with all white pixels } (P_1, P_2, P_3, \dots, P_n)}$$

Note4. Definition of response time

The response time is defined as the LCD optical switching time interval between “White” state and “Black”state. Rise time (Tr) is the time between photo detector output intensity changed from 90% to 10%. And fall time (Tf) is the time between photo detector output intensity changed from 10% to 90%.

For additional information see FIG1.

Note5. Definition of color chromaticity (CIE1931)

CIE (x,y) chromaticity, The x,y value is determined by screen active area center position P5. For more information see FIG.2.

Note6. Definition of viewing angle

Viewing angle is the angle at which the contrast ratio is greater than 10. Angles are determined for the horizontal or x axis and the vertical or y axis with respect to the z axis which is normal to the LCD surface. For more information see FIG.3.

For viewing angle and response time testing, the testing data is base on Autronic-Melchers’s ConoScope or DMS series Instruments or compatible.

FIG.1. The definition of response Time




FIG.2. Measuring method for contrast ratio, surface luminance,

luminance uniformity, CIE (x,y) chromaticity

Size : S≤5”(see Figure a) A : 5 mm B : 5 mm

H,V : Active area

Light spot size $\phi=5\text{mm}$ (BM-5) or $\phi=7.7\text{mm}$ (BM-7) 50cm distance or compatible distance from the LCD surface to detector lens.

test spot position : see Figure a.

measurement instrument : TOPCON’s luminance meter BM-5 or BM-7 or compatible (see Figure c).




Figure a

Size : 5" $S \le 12.3''$(see Figure b) H,V : Active area

Light spot size $\phi=5\text{mm}$ (BM-5) or $\phi=7.7\text{mm}$ (BM-7)50cm distance or compatible distance from the LCD surface to detector lens.

test spot position : see Figure b.

measurement instrument : TOPCON's luminance meter BM-5 or BM-7 or compatible (see Figure c).






FIG.3.The definition of viewing angle




8. Environmental / Reliability Tests

No	Test Item	Condition	Remarks
1	High Temperature Operation	Ts= +70°C, 96hrs	Note 1 IEC60068-2-2, GB2423.2-89
2	Low Temperature Operation	Ta= -20°C, 96hrs	Note 2 IEC60068-2-1 GB2423.1-89
3	High Temperature Storage	Ta= +80°C, 120hrs	IEC60068-2-2 GB2423.2-89
4	Low Temperature Storage	Ta= -30°C, 120hrs	IEC60068-2-1 GB/T2423.1-89
5	High Temperature & Humidity Storage	Ta= +60°C, 90% RH max, 120 hours	IEC60068-2-3 GB/T2423.3-2006
6	Thermal Shock (Non-operation)	-20°C 30 min ~ +60°C 30 min Change time: 5min, 30 Cycle	Start with cold temperature, end with high temperature IEC60068-2-14, GB2423.22-87
7	Electro Static Discharge (Operation)	C=150pF, R=330 Ω, 5 points/panel Air:±8KV, 5 times; Contact: ±4KV, 5 times; (Environment: 15°C ~ 35°C, 30% ~ 60%, 86Kpa ~ 106Kpa)	IEC61000-4-2 GB/T17626.2-1998
8	Vibration (Non-operation)	Frequency range: 10~55Hz, Stroke: 1mm Sweep: 10Hz~55Hz~10Hz 2 hours for each direction of X .Y. Z. (package condition)	IEC60068-2-6 GB/T2423.5-1995
9	Shock (Non-operation)	60G 6ms, ± X, ±Y, ± Z 3 times for each direction	IEC60068-2-27 GB/T2423.5-1995
10	Package Drop Test	Height: 80 cm, 1 corner, 3 edges, 6 surfaces	IEC60068-2-32 GB/T2423.8-1995


- Note: 1. Ts is the temperature of panel's surface.
2. Ta is the ambient temperature of sample.
3. The size of sample is 5pcs.

9. Mechanical Drawing



10. Packing

Packing Method



11. TFT-LCD Module Inspection Criteria

11.1 Scope

The incoming inspection standards shall be applied to TFT –LCD Modules (hereinafter Called "Modules") that supplied by LCD Mall Limited.

11.2 Incoming Inspection

The customer shall inspect the modules within twenty calendar days of the delivery date (the inspection period) at its own cost. The result of the inspection (acceptance or rejection) shall be recorded in writing, and a copy of this writing will be promptly sent to The seller, If the results of the inspecting from buyer does not send to the seller within twenty Calendar days of the delivery date. The modules shall be regards as acceptance.

Should the customer fail to notify the seller within the inspection period, the buyers Right to reject the modules shall be lapsed and the modules shall be deemed to have Been accepted by the buyer

11.3 Inspection Sampling

- 3.1. Lot size: Quantity per shipment lot per model
 - 3.2. Sampling type: Normal inspection, Single sampling
 - 3.3. Inspection level: II
 - 3.4. Sampling table: MIL-STD-105E
 - 3.5. Acceptable quality level (AQL)
- Major defect: AQL=0.65 Minor defect: AQL=1.00

11.4 Inspection Conditions

4.1 Ambient conditions:


- a. Temperature: Room temperature $25\pm 5^{\circ}\text{C}$
- b. Humidity: $(60\pm 10)\% \text{RH}$
- c. Illumination: Single fluorescent lamp non-directive (300 to 700 Lux)

4.2 Viewing distance

The distance between the LCD and the inspector's eyes shall be at least $35\pm 5 \text{ cm}$.

4.3 Viewing Angle

U/D: $45^{\circ}/45^{\circ}$, L/R:



$45^{\circ}/45^{\circ}$


11.5 Inspection Criteria





Defects are classified as major defects and minor defects according to the degree of Defectiveness defined herein.

11.5.1 Major defect


Item No	Items to be inspected	Inspection Standard
5.1.1	All functional defects	1) No display 2) Display abnormally 3) Short circuit 4) line defect
5.1.2	Missing	Missing function component
5.1.3	Crack	Glass Crack

11.5.2 Minor defect

Item No	Items to be inspected	Inspection standard	
5.2.1	Spot Defect Including Black spot White spot Pinhole Foreign particle Polarizer dirt	For dark/white spot is defined $\phi = (x+y) / 2$ 	
		Size ϕ (mm)	Acceptable Quantity
		$\phi \leq 0.2$	Ignore
		$0.2 < \phi \leq 0.5$	3
		$0.5 < \phi$	Not allowed

5.2.2	Line Defect Including Black line White line Scratch	Define: 		
		Width(mm) Length(mm)		Acceptable Quantity
		W≤0.05		Ignore
		0.05 < W≤0.1 L≤2.5		3
		0.1 < W, or L>2.5		Not allowed
5.2.3	Polarizer Dent/Bubble	Sizeφ(mm)		Acceptable Quantity
		φ≤0.2		Ignore
		0.2 < φ≤0.3		2
		0.3 < φ≤0.5		1
		0.5 < φ		Not allowed
		Total QTY		3
5.2.4	Electrical Dot Defect	Bright and Black dot define:  and 		
				
		Two Adjacent Dot		
		Inspection pattern: Full white、 Full black、 Red、 green and blue screens		
		Item		Acceptable Quantity
		I	O	Note
Black dot defect		2		

		Bright dot defect	1	(5mm≤Distance)
		Two Adjacent Dot	1	
		There or more Adjacent Dot	Not allowed	
		Total Dot	2	
5.2.5	Glass defect	<p>1. Corner Fragment:</p>		
		Size(mm)	Acceptable Quantity	
		X≤3mm Y≤1mm Z≤T	Ignore T: Glass thickness X: Length Y: Width Z: thickness	
		<p>2. Side Fragment:</p>		
		Size(mm)	Acceptable Quantity	
		X≤5.0mm Y ≤1mm Z≤T	T: Glass thickness X: Length Y: Width Z: thickness	





I area & O area

- Note:
- 1). Dot defect is defined as the defective area of the dot area is larger than 50% of the dot area.
 - 2). The distance between two bright dot defects (red, green, blue, and white) should be larger than 15mm.
 - 3). The distance between black dot defects or black and bright dot defects should be more than 5mm apart.
 - 4). Polarizer bubble is defined as the bubble appears on active display area. The defect of polarizer bubble shall be ignored if the polarizer bubble appears on the outside of active display area.

11.6 Mechanics specification

As for the outside dimension, weight of the modules, please refer to product specification
For more details



12. Precautions for Use of LCD modules

12.1 Handling Precautions

12.1.1. The display panel is made of glass. Do not subject it to a mechanical shock by dropping it from a high place, etc.

12.1.2. If the display panel is damaged and the liquid crystal substance inside it leaks out, be sure not to get any in your mouth, if the substance comes into contact with your skin or clothes, promptly wash it off using soap and water.

12.1.3. Do not apply excessive force to the display surface or the adjoining areas since this may cause the color tone to vary.

12.1.4. The polarizer covering the display surface of the LCD module is soft and easily scratched. Handle this polarizer carefully.

12.1.5. If the display surface is contaminated, breathe on the surface and gently wipe it with a soft dry cloth. If still not completely clear, moisten cloth with one of the following solvents:

Isopropyl alcohol & Ethyl alcohol

Solvents other than those mentioned above may damage the polarizer. Especially, do not use the following: Water & Ketene & Aromatic solvents

12.1.6. Do not attempt to disassemble the LCD Module.

12.1.7. If the logic circuit power is off, do not apply the input signals.

12.1.8. To prevent destruction of the elements by static electricity, be careful to maintain an optimum work environment.

12.1.8.1. Be sure to ground the body when handling the LCD Modules.

12.1.8.2. Tools required for assembly, such as soldering irons, must be properly ground.

12.1.8.3. To reduce the amount of static electricity generated, do not conduct assembly and other work under dry conditions.

12.1.8.4. The LCD Module is coated with a film to protect the display surface. Be care when peeling off this protective film since static electricity may be generated.

12.2 Storage Precautions

12.2.1. When storing the LCD modules, avoid exposure to direct sunlight or to the light of fluorescent lamps.

12.2.2. The LCD modules should be stored under the storage temperature range. If the LCD modules will be stored for a long time, the recommend condition is:

Temperature : 0°C ~ 40°C Relatively humidity: ≤80%

12.2.3. The LCD modules should be stored in the room without acid, alkali and harmful gas.

12.3 Transportation Precautions

The LCD modules should be no falling and violent shocking during transportation, and also should avoid excessive press, water, damp and sunshine.